

**Model #**

**SuperLite™ C/P & C/SP**

**SuperLite C/P Premium Ceramic Glazing Solution**  
**SuperLite C/SP Safety Premium Ceramic Glazing Solution**

20/30/45/60/90/120/180 Minute Fire Protective Glazing

**For Use In**

Advantage models # T4G, T4G-G, 784G, 84G-Z#,  
or any approved fire-rated framing system.

**Specifications**

Thickness : 3/16" (5mm)  
Weight: 2.4 lbs./ sq. ft.  
Appearance : Slight amber with some surface irregularity.

**Other Information**

- Positive-pressure fire-rated.
- Tough and durable safety filmed glazing that meets the highest federal standard for impact safety, CPSC 16CFR 1201 Cat. II, which requires withstanding 400 ft. lbs. of impact.
- Available in large sizes up to 43" x 77".
- Can be insulated or lightly sandblasted.

**UL Listed**

Fire-Rating Information:  
UL 10B, UL 10C, UBC 7-2, NFPA 252.

**SuperLite C/P Premium Ceramic Glazing**

20-45 minutes : For windows / transoms 3,476 sq. in.  
(up to 77" W x 77" H), stop height 5/8".

**SuperLite C/SP Safety Premium Ceramic Glazing**

20-45 minutes : For doors, 3,476 sq. in. max. lite area  
(up to 60" W x 77" H), stop height 5/8".  
For sidelites, windows / transoms, 3,476 sq. in. max. lite area  
(up to 77" W x 77" H), stop height 5/8".

60-180 minutes : For doors (temp. rise), 100 sq. in. max. lite area  
(up to 12" W x 33" H), stop height 5/8".

*Note: Ceramics are not barriers to radiant heat.*



**ADVANTAGE**  
**LITES & LOUVERS**

**ADVANTAGE LITES & LOUVERS, INC.**  
415 Concord Avenue, Bronx, NY 10455 U.S.A  
Tel: 718-585-3230 Fax: 718-292-2243 Web: www.a-ll.com



A ZERO INTERNATIONAL COMPANY  
www.zerointernational.com

Since 1923